

Lizerna Conc.

Neutral fat remover



Properties

- special grease-dissolving formulation for every wash
- effective already from 40 °C
- versatile use as emulsifier, wetting agent and washing power booster in all washing systems
- gentle for colors and fabrics

Application

Lizerna Conc. can be mixed with water in any ratio, remains low viscosity and does not go through a gel phase. Even at 40 °C Lizerna Conc. already achieves good grease removal, although this improves significantly as the temperature rises.

The product can be added manually or via liquid dosing systems typical of the laundry. It is suitable both for prewashing and, in the case of extreme soiling, as an additive in the main wash.

The dosage recommendation depends on the application. When used as a grease solvent or washing booster, the dosage table below must be observed.

As a wetting agent, the product is dosed at 2-3 g / kg dry wash, and as an emulsifier for heavily pigment-contaminated laundry at 15-20 g / kg dry wash.

Dosing	Degree of contamination		
	light	middle	heavy
Water hardness			
0 - 8.4	2	4	8
8.5 - 14	4	8	10
> 14	8	10	15

The application quantity refers to g / kg dry laundry.
You can find out the degree of hardness or water hardness in degrees of German hardness from your local water company.

Technical data

Density (20°C)	pH-value
1,00 kg / l	7,00 - 8,00 ln concentrate

Notes

Storage should be frost-proof, although the solidified products can be reused after thawing without loss of quality.

For commercial use only. This leaflet is for non-binding information only. The information is based on our current knowledge and experience. In any case, the user is obliged to carry out his own tests and trials to check the suitability of the products for his intended processes and purposes. The information in this leaflet does not constitute a guarantee for the quality and durability of the goods to be supplied by us. We reserve the right to make technical changes within the scope of what is reasonable. The current version of the corresponding EU safety data sheet must also be observed.